

First Choice Alkali Resistant Plaster Primer

First Choice Alkali Resistant Plaster Primer is an economical solvent based white pigmented primer/sealer which is formulated to resist the effects of alkalinity on subsequent coats of paint.

USES:

First Choice Alkali Resistant Plaster Primer is recommended for use on brick, plaster, concrete, fibre-cement surface, rhinolite and masonry surfaces.

SPECIFICATION OR RECOMMENDED PAINT SYSTEM:

1. Surface preparation and application : Essential for good paint performance is a sound substrate that has been properly prepared and cleaned. The standard conditions for the preparation of plastered/masonry surfaces apply.
2. Surface preparation for old/previously painted masonry surfaces: Previously painted surfaces in poor condition must be stripped back to a firm base or the original substrate. All lime washed/distempered surfaces must be removed. All surfaces must be clean, dry and free of dirt and surface contamination before any application of paint.

PROPERTIES:

APPLICATION:	Brush or Roller
CLEANING SOLVENT:	Mineral Turpentine
THINNING SOLVENT:	Thinning not recommended
SPREADING RATE:	PRIMER COAT : 6-8 m ² per litre (depending on surface porosity) FINAL COAT : N/A
DRYING TIMES:	SURFACE DRY : 1-2 hours HARD DRY : 4 hours OVERCOATING : 16 hours
PACK SIZE:	1L, 5L, 20L
COLOUR RANGE:	White only
SPECIFIC GRAVITY:	1,13 + 0,05 kg per litre
VISCOSITY:	75-80 KU
FLASH POINT:	>35° C
FINISH:	Matt