

Warrior First Choice Roof Paints

First Choice Roof Paints are acrylic emulsion based paints using light-fast pigments with easy application, good re-coating properties and excellent durability.

USES:

First Choice Roof Paint can be used on cement, fibre cement, concrete tiles as well as on primed corrugated or IBR roofing. It is also suitable for primed galvanised iron products.

SPECIFICATION OR RECOMMENDED PAINT SYSTEM:

- a) When used on concrete roof tiles or new fibre cement roof sheets, apply one coat of First Choice Alkali Resistant Plaster Primer, or First Choice Roof Paint thinned 10% by volume with water, as a primer/sealer. Thereafter apply two coats of First Choice Roof Paint as supplied to finish.
- b) When used on New Galvanized Iron products, the surface must first be cleaned with Warrior Galvanized Iron Cleaner. Wash and dry to a clean surface. Apply one coat of Warrior Metal Etch Primer. Allow drying for at least 4 hours. Finish with two coats of First Choice Roof paint to colour of choice

PROPERTIES:

APPLICATION: Brush, Roller, and Spray

CLEANING SOLVENT: Water

THINNING SOLVENT: Water

SPREADING RATE: PRIMER COAT: 4-6 m² per litre

FINAL COAT: Depending on surface conditions between 6-8 m² per litre

DRYING TIMES: SURFACE DRY: 30 min-1 hour

HARD DRY: 2-3 hours

OVERCOATING: 3-4 hours

PACK SIZE: 5L, 20L

COLOUR RANGE: Rich Red, Slate, Midnite and Canyon

RELATIVE DENSITY 1,10 ± 0,05 kg per litre

VISCOSITY: 100-105 KU

FLASH POINT: Non flammable

FINISH: Light sheen

GENERAL:

- a) For new work apply two coats of roof paint.
- b) For best results it is recommended to repaint every five years as maintenance.
- c) This product is supplied ready for use but can be thinned up to 15% for porous surfaces
- d) It is important that this product be thoroughly mixed with a flat paddle before use.