

First Choice Universal Undercoat

First Choice Universal Undercoat is an economical general purpose alkyd based white undercoat with excellent flow, levelling and brushing properties.

USES:

First Choice Universal Undercoat provides a sound key between the primer coat and subsequent finishing with decorative enamels and acrylics. It can also be used for interior and exterior purposes on a wide range of primed substrates.

SPECIFICATION OR RECOMMENDED PAINT SYSTEM:

1. When used as an undercoat: Ensure that the surface is clean, dry and free from dust and all foreign matter. Apply one coat of First Choice Universal Undercoat. Allow to dry for 12-16 hours.
2. When used as an intermediate coat: The surface to be coated must be lightly sanded to form a key. Apply one coat of First Choice Universal Undercoat. Allow to dry for 12-16 hours.

PROPERTIES:

| | |
|-------------------|--|
| APPLICATION: | Brush, Roller and Spray* |
| CLEANING SOLVENT: | Mineral Turpentine |
| THINNING SOLVENT: | Mineral Turpentine |
| SPREADING RATE: | 6-7 m ² per litre |
| DRYING TIMES: | SURFACE DRY 3-4 hours HARD DRY : 12-16 hours OVERCOATING : overnight |
| PACK SIZE: | 1L, 5L, 20L (200L on request) |
| COLOUR RANGE: | White only |
| SPECIFIC GRAVITY: | +1,2 kg per litre |
| VISCOSITY: | 75-80 KU |
| FLASH POINT: | >35°C |
| FINISH: | Matt |

GENERAL INFORMATION:

*For spray application, contact our Technical Department.

- a) This product may only be over coated with conventional single pack decorative enamels and acrylics.
- b) It is important that this product be thoroughly mixed with a flat paddle before use. It is important that this product be thoroughly mixed with a flat paddle before use