

First Choice Super Matt

First Choice Super Matt is a durable matt acrylic paint with reasonable wash ability and good overall properties.

USES:

First Choice Super Matt is an economical interior/exterior P.V.A., suitable for use as a finishing coat on primed masonry surfaces.

SPECIFICATION OR RECOMMENDED PAINT SYSTEM:

- a) Raw plaster - Apply one coat First Choice Alkali Resistant Plaster Primer or First Choice High Cover PVA. Allow to dry for ± 3 hours. Thereafter apply two coats First Choice Super Matt.
- b) Previously Painted Surfaces - Apply 2 coats of First Choice Super Matt. Allow 3-4 hours drying time between coats.

PROPERTIES:

APPLICATION:	Brush, Roller
CLEANING SOLVENT:	Water
THINNING SOLVENT:	Water
SPREADING RATE:	PRIMER COAT : 4-6 m ² per litre FINAL COAT : $\pm 6-8$ m ² per litre (depending on surface porosity)
DRYING TIMES:	SURFACE DRY : 1 hour HARD DRY: 3-4 hours OVERCOATING : 3-4 hours
PACK SIZE:	5L, 20L (200L on request)
COLOUR RANGE:	White and a selected range of pastels. Deep colours will be available from February 2007
VISCOSITY:	120-125 KU
SCRUB RESISTANCE:	4000 Oscillations
FLASH POINT:	Non Flammable
RELATIVE DENSITY:	1,40 \pm 0,05 kg per litre